

FULL SYNTHETIC

RACING **ROTARY ENGINE OIL 10W-30**

This formulation has been specifically engineered to meet the unique requirements of a rotary engine. The technology base for this formulation goes back to the first & only 24 Le Mans race winner using a rotary engine for which IDEMITSU developed the winning oil.

- Allows for Better Sealing of the Chamber, Facilitating More Power Generation
- Extends the Life of Turbochargers by Reducing Bearing Coking
- Minimizes Exhaust Port Clogging
- Superior Shear Stability
- Exceptional Wear Protection & Durability to Protect Main Bearing and Eccentric Shaft
- Contains Special Molybdenum Agents to Reduce Friction, Which Increases Horsepower & Torque

Application:

- Formulated Specifically For High Performance Rotary Engines
- Compatible with turbo charged and super charged applications
- Compatible with Methanol Alcohol and Gasoline Fuel
- Fill Crankcase to Manufacturer's Recommended Level

Characteristics:

Exceeds API Service Class SM

SAE Grade:	10W-30
Viscosity @ 40°C	65.69 cSt
@ 100°C	11.19 cSt
Viscosity Index:	164
CCS Viscosity @ -25°C	4,001
Pour Point:	-45°C
Flash Point:	260°C

Packaging:

Quart (.946 L)



IDEMITSU Racing USA

Manufactured & Distributed by Idemitsu Lubricants America Corporation

Headquarters:

701 Port Rd.,
Jeffersonville, IN 47130
www.idemitsu-usa.com

Sales:

2041 Rosecrans Ave., Suite 355
El Segundo, CA 90245
(310) 563-1930
lasales@ilacorp.com