FULL SYNTHETIC



ROTARY ENGINE OIL 20W-50

This formulation has been specifically engineered to meet the unique requirements of a rotary engine. The technology base for this formulation goes back to the first & only 24 Le Mans race winner using a rotary engine for which IDEMITSU developed the winning oil.

- Allows for Better Sealing of the Chamber, Facilitating More Power Generation
- Extends the Life of Turbochargers by Reducing Bearing Coking
- Minimizes Exhaust Port Clogging
- Superior Shear Stability
- Exceptional Wear Protection & Durability to Protect Main Bearing and Eccentric Shaft
- Contains Special Molybdenum Agents to Reduce Friction, Which Increases Horsepower & Torque

Application:

- Formulated Specifically For High Performance Rotary Engines
- Compatible with turbo charged and super charged applications
- Compatible with Methanol Alcohol and Gasoline Fuel
- Fill Crankcase to Manufacturer's Recommended Level

Characteristics:

Exceeds API Service Class SM

SAE Grade: 20W-50 Viscosity @ 40°C 130 cSt

@ 100°C 18.62 cSt

Viscosity Index: 161
CCS Viscosity @ -15°C 4,486
Pour Point: -45°C
Flash Point: 250°C

Packaging:

Quart (.946 L)

IDEMITSU Racing USA

Manufactured & Distributed by Idemitsu Lubricants America Corporation

Headquarters: Sales:

701 Port Rd., Jeffersonville, IN 47130 www.idemitsu-usa.com 2041 Rosecrans Ave., Suite 355 El Segundo, CA (310) 563-1930 lasales@ilacorp.com

IDEMITSU